

Oale de condens

Supape de sens cu piston

Oale de condens termodinamice



041-042 fara filtru

043-044 cu filtru

Mod. 179 EN ASME/FNPT ASME/SW

Mod. 041 EN ASME/FNPT ASME/SW

Conexiune: Filet interior GAS
Filet interior NPT
Capete sudate
R: 1/4" pana la 2"
Material: ■ Alama PN-200
■ Otel turnat PN-250
Etansare: ■ Otel inoxidabil PN-250
● Metal

Supapa de sens cu piston si arc.

Mod. 043 EN ASME/FNPT ASME/SW

Conexiune: Filet interior GAS
Filet interior NPT
Capete sudate
R: 1/2" pana la 1"
Material: ■ Otel inoxidabil PMA. 63 bar
Etansare: ● Metal

Mod. 042 EN ASME/ANSI

Mod. 044 EN ASME/ANSI

Conexiune: Flansa x Flansa
DN: 15 pana la 25
Material: ■ Otel inoxidabil PMA. 63 bar
Etansare: ● Metal

Se utilizeaza pentru eliminarea condensului.
Se folosesc in: instalatiile de abur, calcatorii, spalatorii, rezervoare de condens, prese cu abur, autoclave pentru vulcanizare, echipamente pentru reducerea presiunii de abur, etc.

In functie de model

In functie de model

