

Indicator de nivel cu unghi de vizualizare reglabil

Indicator de nivel cu unghi de vizualizare fix



Mod. 666 EN
Indicatoare de nivel

Conexiune: Flansa
DN: 20

Material: Fonta PN-16
 Fonta nodulara PN-40. 350°C
 Otel turnat PN-40
 Otel inoxidabil PN-40

Etansare: Metal

Robinet de evacuare: Mod. 999 3/8" prindere cu inel taietor si/sau cu niplu filetat



Mod. 466 EN
Indicatoare de nivel

Conexiune: Flansa
DN: 20

Material: Fonta PN-16
 Fonta nodulara PN-40. 350°C
 Otel turnat PN-40
 Otel inoxidabil PN-40

Etansare: Metal

Mod.166-EC EN

Corp indicator de nivel cu unghi de vizualizare reglabil

Conexiune: Tija rotunda Ø 20 mm.
Numar de corpuri: 0 pana la X

Material: Otel turnat PN-16. PN-40
 Otel inoxidabil PN-40

Se folosesc la cazane, recipiente, cisterne, rezervoare,...etc., pentru a controla nivelul lichidelor.
Un vizor poliprismatic permite vizualizarea clara a nivelului de lichid.

In functie de model



-60°C pana la +400°C



40,00 bar



Abur/Gaze/Lichide

Mod.166-ER EN

Corp indicator de nivel cu unghi de vizualizare fix

Conexiune: Tija patrata cu latura patraturului de 18 mm.
Numarul de corpuri: 0 pana la X

Material: Otel turnat PN-16. PN-40
 Otel inoxidabil PN-40

Robinet de evacuare: Mod. 999 3/8" prindere cu inel taietor

Se folosesc la cazane, recipiente, cisterne, rezervoare,...etc., pentru a controla nivelul lichidelor.
Un vizor poliprismatic permite vizualizarea clara a nivelului de lichid.

In functie de model



-60°C pana la +400°C



40,00 bar



Abur/Gaze/Lichide